












Accessories

| Picture | Description | Unit | Order No. |
|-------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------|-----------|
|  | D50 accessory kit | Set | EX655 |
| | <ul style="list-style-type: none"> • Include EX642-3、EX627、EX620、EX602、EX603 • Optional | | |
|  | Explosion proof conductive hose | Pcs | EX642-3 |
| | <ul style="list-style-type: none"> • Meet to ATEX and RoHS directive • Size: $\Phi 38\text{mm}$ • Length: 3m • With D70/D40 stainless steel reducer • Optional | Please mark out length when ordering. Eg: EX642-6 standards for 6m | |
|  | D38x450 Explosion proof drag | Set | EX620 |
| | <ul style="list-style-type: none"> • For clean floor easily. • Made from conductive plastic material • Size: $\Phi 38\text{mm}$ • Width: 450mm • Optional | | |
|  | D38 SUS 304 handle pipe | Set | EX627 |
| | <ul style="list-style-type: none"> • SUS 304 • Size : $\Phi 38\text{mm}$ • Length : 1.3m • Optional | | |
|  | Conductive plastic flat suction nozzle | Pcs | EX602 |
| | <ul style="list-style-type: none"> • Made from conductive plastic material • Size : $\Phi 38\text{mm}$ • Length : 240m • Optional | | |





Remark: Please use TOP company original accessory, otherwise will affect machine guarantee period.

Accessories

| Picture | Description | Unit | Order No. |
|-------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------|-----------|
|  | D38-500 SUS304 flat suction nozzle <ul style="list-style-type: none"> • SUS 304 • Size: $\Phi 38\text{mm}$ • Length: 500m • Optional | Pcs | EX630 |
|  | D32 Conductive flat suction nozzle <ul style="list-style-type: none"> • Made from conductive plastic material • Size: $\Phi 32\text{mm}$ • Optional | Pcs | EX623 |
|  | Conductive plastic brush <ul style="list-style-type: none"> • Made from conductive plastic material • Size: $\Phi 43\text{mm}$ • Optional | Pcs | EX603 |
|  | Anti-static HEPA filter <ul style="list-style-type: none"> • Minimum efficiency of 99.95% on 0.3 microns • Size : $\Phi 210 \times \Phi 130 \times 200\text{mm}$ • One included | Set | EX615 |
|  | Anti-static medium filter bag <ul style="list-style-type: none"> • Filter surface reach to 20000cm^2 • Size : $\Phi 43\text{mm}$ • One included | Set | EX605 |
|  | D70/40 SUS304 reducer <ul style="list-style-type: none"> • SUS 304 • Size : From $\Phi 70\text{mm}$ to $\Phi 40$ • Optional | Pcs | EX632 |

Remark: Please use TOP company original accessory, otherwise will affect machine guarantee period.

Accessories

| Picture | Description | Unit | Order No. |
|-------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------|------|------------------|
| Explosion proof grounding clamp | | Set | PE10-5 |
|  | <ul style="list-style-type: none">• Spiral grounding cable is 5m (extendable) | Set | PE10-5 |
| | <ul style="list-style-type: none">• One included | | |
| Grounding plug | | Set | PED6-5000V |
|  | <ul style="list-style-type: none">• Diameter 6mm | Set | PED6-5000V |
| | <ul style="list-style-type: none">• One pug end, one Φ5 wiring nose.• Length: 5000mm• Optional | | |
| Explosion proof plug | | Pcs | CZ0251-740600-01 |
|  | <ul style="list-style-type: none">• IECEx and ATEX certified | Pcs | CZ0251-740600-01 |
| | <ul style="list-style-type: none">• Used for Zone 1 Zone 2 and Zone 21 Zone 22• Specification: 16A 200-250V 1P+N+PE 6h• Optional | | |
| Explosion proof socket | | Set | CZ0251-440600-01 |
|  | <ul style="list-style-type: none">• IECEx and ATEX certified | Set | CZ0251-440600-01 |
| | <ul style="list-style-type: none">• Used for Zone 1 Zone 2 and Zone 21 Zone 22• Specification: 16A 200-250V 1P+N+PE 6h• Optional | | |

Remark: Please use TOP company original accessory, otherwise will affect machine guarantee period.