Accessories

Picture	Description	Unit	Order No.
	D38 accessory kit	Set	EX656
	• Include EX643-3、NE710、EX621、NE704、EX646 • Optional		
	D50 accessory kit	Set	EX655
	• Include EX642-3、EX627、EX620、EX602、EX603 • Optional		
	Explosion proof conductive hose	Pcs	EX642-3
	• Meet to ATEX and RoHS directive • Size：Φ38mm • Length：3m • With D70/D40 stainless steel reducer • Optional		Please mark out length when ordering. Eg: EX642-6 standards for 6m
	Explosion proof conductive hose	Pcs	EX643-3
	• Meet to ATEX and RoHS directive • Size：Φ50mm • Length：3m • With D70/D50 stainless steel reducer • Optional		Please mark out length when ordering. Eg: EX643-6 standards for 6m
	D38×450 Explosion proof drag	Set	EX620
	• For clean floor easily. • Made from conductive plastic material • Size：Φ38mm • Width：450mm • Optional		

Remark: Please use TOP company original accessory, otherwise will affect machine guarantee period.

Accessories

Picture	Description	Unit	Order No.
	D50-450 drag	Pcs	EX621
	• Good suction ability and smart using • Two rubber lines for liquid cleaning • Size: Φ50mm • Width: 450mm • Optional		
	D38×450 SUS 304 drag	Pcs	EX637
	• Good suction ability and smart using • Two rubber lines for liquid cleaning • Size: Φ38mm • Width: 450mm • Optional		
	D50×450 SUS 304 drag	Pcs	EX628
	• Good suction ability and smart using • Two rubber lines for liquid cleaning • Size: Φ50mm • Width: 450mm • Optional		
	D38 SUS 304 handle pipe	Pcs	EX627
	• Size: Φ38mm • Length: 1.3m • Optional		
	D50 Aluminium handle	Pcs	NE710
	• Surface anodization • Size:Φ50mm • Length: 1.3m • Optional		
	D50 SUS304 handle	Pcs	EX624
	• Size: Φ50mm • Length: 1.3m • Optional		

Remark: Please use TOP company original accessory, otherwise will affect machine guarantee period.

Accessories

Picture	Description	Unit	Order No.
	Conductive plastic flat suction nozzle	Pcs	EX602
	• Made from conductive plastic material • Size: Φ38mm • Length : 240m • Optional		
	D38-500 SUS304 suction nozzle	Pcs	EX630
	• Size: Φ38mm • Length: 500mm • Optional		
	D50-500 SUS304 suction nozzle	Pcs	EX631
	• Size: Φ50mm • Length: 500mm • Optional		
	D50-500 Aluminium suction nozzle	Pcs	NE704
	• Surface anodization • Size: Φ50mm • Length: 500mm • Optional		
	D50-1000 Aluminium suction nozzle	Pcs	NE705
	• Surface anodization • Size: Φ50mm • Length: 1000mm • Optional		
	D32 Conductive flat suction nozzle	Pcs	EX623
	• Made from conductive plastic material • Size: Φ32mm • Optional		

Remark: Please use TOP company original accessory, otherwise will affect machine guarantee period.

Accessories

Picture	Description	Unit	Order No.
	Conductive plastic brush	Pcs	EX603
	• Made from conductive plastic material • Size: Φ43mm • Optional		
	Conductive plastic brush	Pcs	EX646
	• Made from conductive plastic material • Size: Φ50mm • Optional		
	Anti-static medium filter bag	Set	EX605
	• Filter surface reach to 20000cm² • Size : Φ43mm • One included		
	Anti-static HEPA filter	Set	EX638
	• Minimum efficiency of 99.95% on 0.3 microns • Size : Φ324×Φ213×225mm • One included		
	D70/40 SUS304 reducer	Pcs	EX632
	• SUS 304 • Size : From Φ70mm to Φ40 • Optional		
	D70/50 SUS304 reducer	Pcs	EX633
	• SUS 304 • Size : From Φ70mm to Φ50 • Optional		

Remark: Please use TOP company original accessory, otherwise will affect machine guarantee period.

Accessories

Picture	Description	Unit	Order No.
	40 SUS 304 hook	Pcs	EX635
	• Size: 40mm • Optional		
	40/50 SUS 304 hook	Pcs	EX636
	• Size: 40mm • Ring size: 50mm • Optional		
	Explosion proof grounding clamp	Set	PE10-5
	• Spiral grounding cable is 5m (extendable) • One included		
	Explosion proof plug	Pcs	CZ0251-750600-01
	• IECEx and ATEX certified • Used for Zone 1 Zone 2 and Zone 21 Zone 22 • Specification: 16A 200-250V、380-415V 3P+N+PE 6h • Optional(4kW)		
	Explosion proof socket	Set	CZ0251-450600-01
	• IECEx and ATEX certified • Used for Zone 1 Zone 2 and Zone 21 Zone 22 • Specification: 16A 200-250V、380-415V 3P+N+PE 6h • Optional(4kW)		
	Explosion proof plug	Pcs	CZ0252-750600-01
	• IECEx and ATEX certified • Used for Zone 1 Zone 2 and Zone 21 Zone 22 • Specification: 16A 200-250V、380-415V 3P+N+PE 6h • Optional(5.5kW、7.5kW)		

Remark: Please use TOP company original accessory, otherwise will affect machine guarantee period.

Accessories

Picture	Description	Unit	Order No.
	Explosion proof socket	Set	CZ0252-450600-01

- IECEx and ATEX certified
- Used for Zone 1 Zone 2 and Zone 21 Zone 22
- Specification: 32A 200-250V、380-415V 3P+N+PE 6h
- Optional (5.5kW、7.5kW)

Remark: Please use TOP company original accessory, otherwise will affect machine guarantee period.